Daily, Weekly, and Monthly Maintenance

The **Connor Stage System** is a high-performance, engineered platform designed for durability, stability, and safety under demanding stage conditions. Its advanced composite surface provides excellent impact resistance, screw retention, and moisture resistance while maintaining a professional matte finish suitable for all types of performances and production environments.

Routine / Daily Maintenance

Dry clean the surface	Use a microfiber dust mop, soft broom, or vacuum to remove dust, grit, and debris. Avoid abrasive pads, stiff bristles brooms, or vacuums with firm bristle rollers used to clean carpet.	Daily (after each use or event)
Daily (after each use or event)	Wipe up liquid spills immediately with a slightly damp cloth or mop . Prevent standing moisture from accumulating on the surface.	As needed
Avoid any pooling liquids	Even though the surface is moisture resistant, standing water can affect seams and subflooring if left unattended.	Continuous
Use walk off mats at high traffic areas	Walk off mats should be placed near all entry ways to remove access dirt, debris, and liquids. These should be cleaned regularly to avoid unnecessary damage to the surface.	Daily / Post-event
Equipment handling	Use soft, non-marking wheels for rolling equipment (e.g., road cases, risers). Avoid dragging or dropping sharp or heavy items directly on the surface.	Always

Regular Cleaning (Weekly / Bi-Weekly)

Neutral pH cleaning	Clean with mild detergent and water only . Use a lightly damp mop or soft brush. Do not use strong solvents, petroleum-based cleaners, or high-pH agents.	
Rinse if needed	If any film or residue remains, rinse with clean water and allow to dry completely.	
Edge & seam check	Examine panel seams and fasteners. Tighten or adjust if panels show movement or minor lift.	
Surface inspection	Look for gouges, scratches, or burn marks . Although highly durable, surface integrity should be preserved through timely repair or replacement of damaged panels.	

Monthly / Periodic Maintenance


Full-surface cleaning	Conduct a deep clean with mild detergent and water, focusing on high usage areas and traffic lanes.	
Inspect subfloor	Examine the Connor Stage Panels for loose fasteners, unevenness, or deflection. Tighten or replace as necessary.	
Evaluate heavy-load zones	Check under rolling equipment and set pieces for pressure indentations or localized wear. Use load-spreading pads or rubber mats as preventive protection.	
Environmental monitoring	Maintain temperature between 60–80°F (16–27°C) and humidity between 40–60% RH to prevent movement or expansion.	
Adhesive management	If stage or gaffers tape is used, remove promptly after use . Avoid harsh adhesive removers or solvents that could dull the surface.	



- 1. Use **neutral pH cleaners** (mild detergent + water)
- 2. Clean spills promptly
- 3. Use **soft cleaning tools** (microfiber, soft mop)
- 4. Inspect joints and subfloor regularly
- 5. Protect with mats under heavy loads
- 6. Maintain temperature and humidity



1. Use petroleum-based solvents, degreasers, or waxes



3. Use abrasive pads, brushes, or steel wool

NO!

- 4. Ignore panel gaps, lifting, or seam wear
- 5. Drag heavy or sharp equipment directly on surface
- 6. Expose to extreme heat or cold without acclimation



